

T-R/N



Product Features

- ✓ High density die-cast aluminum light body, corrosion resistance.
- ✓ Large capacity lithium iron phosphate battery, large size five grid polycrystalline photovoltaic panels, national standard precision waterproof wire.
- ✓ High bright , high light efficiency, low light decay, no ultraviolet radiation, life up to 50,000 hours.
- ✓ Toughened glass mask, scientific light distribution, high light transmittance, impact resistance, flame retardant, strong thermal stability.
- ✓ Function control: wireless remote control,intelligent light control ,power display and unimpeded quick charge.
- ✓ Waterproof grade IP66, physical structure waterproof ,sealing tape.
- ✓ Suitable for villages, roads, courtyards, villas, resorts, etc.....

Product Parameters

Model	Power	Number of leds	Battery	Panel power	Lighting area	Panel size	Light size
T-R30/N	30W	SMD/70PCS	3.2V5000mAh	5V/12W	40m ²	360X172X17mm	200X180X42mm
T-R60/N	60W	SMD/80PCS	3.2V10000mAh	5V/18W	60m ²	340X290X17mm	228X196X45mm
T-R100/N	100W	SMD/120PCS	3.2V16500mAh	5V/25W	80m ²	340X385X17mm	270X237X45mm
T-R200/N	200W	SMD/224PCS	3.2V27500mAh	5V/35W	100m ²	350X520X17mm	318X288X50mm
T-R300/N	300W	SMD/360PCS	3.2V33000mAh	5V/40W	150m ²	350X630X17mm	350X385X55mm